


FORD TRUCKS 1848T EURO6



Basic Features

| | |
|----------------|-----------------------------|
| Vehicle Type | Tractor |
| Axle | 4x2 |
| Emission | Euro 6 |
| Cabin Type | Extra High Roof Sleeper Cab |
| Wheelbase (mm) | 3600 |

Engine

| | |
|--------------------|----------------------------|
| Type | Ecotorq 12,7 lt |
| Displacement (cc) | 12740 |
| Diameter x Stroke | 130 mm x 160 mm |
| Power | 480 PS (353 kW) / 1800 rpm |
| Torque | 2500 Nm / 1000 - 1200 rpm |
| Compression Ratio | 17 +/- 0,5 : 1 |
| Oil Filling Volume | 50 L |
| Coolant Volume | 37 L (57 L with Intarder) |

Transmission

| | |
|------------------------|-----------------------------------|
| Clutch | 430mm Single Disc |
| Automated Transmission | ZF 12 TX 2620 TRAXON (16,688 - 1) |

Steering

Power Assisted Single Circuit

Chassis

| | |
|--|---|
| Chassis Thickness (mm) | 8mm with Local Reinforcement |
| Chassis Strength | 500MPa |
| Suspension (Front/Rear) | 90 mm Parabolic Leaf Springs / Air Suspension |
| Axle | Single Reduction |
| Axle Ratio - 1200 mm 5 th Wheel | 2,64 |
| Axle Ratio - 1100 mm 5 th Wheel | 2,47 |
| Tyres - 1200 mm 5 th Wheel | 295/80 R22.5 |
| Tyres - 1100 mm 5 th Wheel | 315/70 R22.5 |
| Wheel Rim | 22,5 x 9 Steel |

Braking System

| | |
|---|---|
| Brakes (Front/Rear) (Ø.mm x mm. Length) | 430 x 45 Disc Brakes |
| Braking System | Dual Brake Circuit – Air Processing Unit with Integrated Oil Separator and Heater |
| Engine Brake Power | max. 340 kW (Engine Level) |
| Intarder Power | max. 600 kW / Continuous 160 kW |

Electrical System

| | |
|----------------------------|---------------------|
| Battery | 24V, 2 x 12V 180 Ah |
| Alternator / Starter Motor | 130 A / 6,5 kW |

Tanks

| | |
|-----------|-----------------|
| Fuel Tank | 600 L Aluminium |
| SCR Tank | 78 L |



Sharing the load

Dimensions (mm)

| | |
|---|--|
| 5 th Wheel Height | 1100 |
| Front Overhang | 1500 |
| Wheelbase | 3600 |
| Overall Length | 6150 |
| Overall Cab Length | 2305 |
| Total Height | 3945 (Extra High Roof) , 3104 (Low Roof) |
| Overall Vehicle Width (Excluding Mirrors) | 2540 |
| Chassis Width | 866 |
| Rear Overhang | 1050 |
| Chassis Height-Front | 225 |
| Chassis Height-Rear | 285 |
| Ground Clearance-Front | 300 |
| Ground Clearance-Rear | 255 |
| Turning Radius | 7500 |

Weights (kg)

| | 1. Axle | 2. Axle | Total |
|---------------------------------|---------|---------|-------|
| Technically Permissible Weights | 7100 | 12600 | 18000 |
| Kerb Weight | 5113 | 1979 | 7092 |
| Payload | 1987 | 10621 | 10908 |
| GVM (Legal) | 7100 | 11500 | 18000 |

STANDARD EQUIPMENT

- Air Conditioner
- Radio/CD Player
- Extra High Roof Cab with Double Bed
- Dry Type Cab Heater
- Air Suspended Cab
- Cruise Control
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Levelling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Electrically Operated Sunroof
- Front and Rear Vehicle Antiroll Bar
- Automated Transmission (with different usage modes)
- Disc Brakes
- Electronic Brake System (EBS) and Anti-Lock Brake System (ABS)
- Active Emergency Brake System (AEBS)
- Electronic Brake Force Control
- Brake Assistant
- Electronic Stability Program (ESP)
- Brake Lining Wear Sensor
- Lane Departure Warning System
- Auto Light Sensor
- Rain Sensor
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
- Switchable Air Compressor for Improved Fuel Economy
- Variable Steering Pump for Improved Fuel Economy
- Hill Launch Assist
- Coupling Force Control
- Front Fog Lamps
- Axle Load Indicator

OPTIONAL EQUIPMENT

- Intarder
- ADR Pack
- Low Roof Sleeper Cab with Single Bed
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry & Wet Type Cab Heater
- Engine Driven PTO
- Transmission Driven PTO & Interior Control Unit
- 5th Wheel Options * : 960, 1050, 1100, 1150, 1200, 1250, 1300 mm
- Spare tyre and carrier
- Jost 5th Wheel
- Dual Fuel Tank (450L)
- Side Skirt
- Spoiler**
- 225 Ah Battery
- Electrically Operated Cab Tilting
- Upper Bed

* 960 mm 5th wheel height is available with Front Tire : 315/60 R 22,5 / Rear Tire: 295/60 R 22,5

* 1050 mm 5th wheel height is available with 315/60 R22,5 tyres

* 1100 mm 5th wheel height is available with 315/70 R22,5 tyres

* 1150 mm 5th wheel height is available with 295/80 R22,5 tyres

* 1200 mm 5th wheel height is available with 295/80 R22,5 or 315/80 R22,5 tyres

* 1250 mm 5th wheel height is available with 295/80 R22,5 tyres

* 1300 mm 5th wheel height is available with 315/80 R22,5 tyres

** Not Available with Low Roof Sleeper Cab Version

This leaflet includes products designed for Ford Trucks vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications.